

Materials Health, Safety and Environmental Data Sheet
(EG)1907/2006, (EG)1272/2008, (EG)453/2010

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY**1.1 Product identification**

Trade name: Lastifil 807
Application: solid MIG/MAG-welding wire for stainless steel and unalloyed steel

1.2 Supplier/Manufacturer:

Name: Lastek Belgium n.v.
Address: Toekomstlaan 50 – B2200 Herentals
Phone/Fax: phone: +32 14/22.57.67 fax.: +32 14/22.31.91 E-mail: info@lastek.be

1.3 Telephone for emergency: +32 14/22.57.67

2. COMPOSITION AND INFORMATION ABOUT CONSTITUENTS

Stainless steel, containing: chromium, nickel, manganese and iron.

3. RISKS

The product self does not give hazardous risks but electric arc welding may create one or more of the following hazards:

- * H332 harmful if inhaled (welding fumes and vapours)
- * H331 toxic if inhaled (carbon monoxide / ozone)
- * H335 may cause respiratory irritation
- * H315 causes skin irritation (UV- and IR-radiation, can cause skin irritation and hot slag can cause burns)
- * H319 causes serious eye irritation (UV / IR-radiation: heat can cause eye irritation, hot slag can cause burns)
- * H242 heating may cause a fire (spatter and sparks)
- * Mechanical risk: wire ends can cause stab-wounds or cuts.
- * Electric shock can kill

4. FIRST AID INSTRUCTIONS

Inhalation: Bring affected person to fresh air, if irritation persists seek medical attention
Eye contact: With opened eye lid flush with plenty of water, reduce exposure to arc
Skin contact: In case of burn flush with plenty of water and call a physician
In case of arc burn: call a physician

5. FIRE FIGHTING INFORMATION

Extinguishing media: The product is non flammable. In case of environmental fire use fire fighting measures that suit the environment and products stored (water, CO₂, sand, fire blanket, etc.).
Extinguishing media to avoid: n.a.
Special fire fighting procedures: n.a.
Hazardous decomposition products: none

6. PRECAUTIONS TO BE TAKEN IN CASE MATERIAL IS RELEASED

Waste disposal method: Professional disposal of welding waste
Cleaning methods: Collect wire and bind together
Personal protection: n.a.

7. HANDLING AND STORING

Handling: fume extraction needed if welding fumes may be released, see section 8
Storing: Dry place
Heavy product; avoid storing in unstable positions to prevent tipping, rolling, slipping and falling. Protect your hands and feet

8. PROTECTION OF PERSONNEL

Technical precautions: during welding the necessary precautions have to be taken:

Use enough and adequate ventilation and local exhaust to keep fumes and gases from the welders breathing zone and the general area. Train the welder to keep his head out of the fumes. Wear suitable protection clothing.

TLV-values: (Belgian list – Royal Decree 19.05.2009 – 91/322/EC - 2000/39/EC - 2006/15/EC)

	CASnr.	TLV
Welding fume	- - -	5 mg/m ³
Iron oxide (fume)	1309-37-1	5 mg/m ³
Manganese and compounds	7439-96-5	0.2 mg/m ³
Chromium (soluble compounds)	7440-47-3	0.05 mg/m ³
Nickel (soluble compounds)	7440-02-0	0.1 mg/m ³

Personal protection:

Respiration protection: use respirable fume respirator or air supplied respirator when welding in confined space or in general work area when local exhaust does not keep exposure below TLV

Eyes: wear helmet or use hand shield with shaded filter lens. The choice of appropriate light filtration will be based on visual acuity and may vary from one individual to another, particularly under different current densities, materials and electrode diameter; suggested filter shade number for gas metal arc welding (MIG/MAG) is 10 to 13.

Hands: wear protective welder gloves to prevent injuries from radiation, sparks and electrical shock

Skin: wear protective welder clothing as aprons, hats, and shoulder protection, arm protectors to prevent injuries from radiation, sparks and electrical shock. Welder may not permit electrical live parts or electrodes to make contact with skin.

9. PHYSICAL AND CHEMICAL DATA

Physical form:	solid, wire	Explosion limits:	n.a.
Odour:	odourless	LEL (lower limit):	
Colour:	shiny metallic	UEL (upper limit):	
pH:	n.a.	Vapour pressure:	n.a.
Boiling point:	n.a.	Specific gravity:	about 8 g/cm ³
Melting point:	> 1400 °C	Solubility in H ₂ O:	nihil
Flash point (method):	n.a.		

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions

Conditions to avoid: n.a.

Products to avoid: Acids and oxidants

Hazardous decomposition products: No fumes or vapour are evolved by this welding wire at normal ambient temperatures but in use (welding)-fumes will be evolved (see section 8)

Hazardous properties: According to IARC (International Agency for Research on Cancer), welding fumes are classified as cancer suspected agent (Group 2B, possibly carcinogenic)

11. TOXICOLOGICAL INFORMATION

General: Prolonged and excessive exposure and inhalation of welding fumes can cause lung disease and affect the respiratory function.

Primary routes of entry: Inhalation of welding fumes

Acute toxicity: A prolonged and excessive exposure to welding fumes can cause: fever, nausea, dizziness, irritation of the eyes and the respiratory tracts or other mucous membranes

Chronic toxicity: A prolonged and excessive exposure to welding fumes can cause: pulmonary/bronchial diseases and/or breathing difficulties. These diseases may also be caused or aggravated.

Overexposure to: Manganese (Mn) can harm the central nervous system and/or aggravate existing diseases.

12. ECOLOGICAL INFORMATION

Ferrous product. Do not expose of in the environment (scrap).

13. WASTE REMOVAL

Rest and residues have to be recuperated, processed or disposed of in an environmentally acceptable manner (scrap).
Cardboard boxes and/or plastic: recycle in accordance with local environmental legislation
Industrial waste number: 120102 (ferrous metallic scraps), 120113 (welding wastes)

14. INFORMATION CONCERNING TRANSPORTATION

UN-nr:	n.a.	IMDG:	n.a.
ADR/RID:	n.a.	IATA:	n.a.

15. LABELLING

H-phrases: H242 / H315 / H319 / H331 / H332 / H335

16. OTHER INFORMATION

This information only refers to the described product and is based on actual knowledge and experience known by us, because operating conditions are unknown to us and does not belong to our sphere of influence.
The product may not be used without written permission for a use other than mentioned in pt.1.
This information may not be taken nor as a guarantee nor as a quality indication of our product.
This material safety information describes the product in relation with safety rules and is not meant as a technical description.
At any time the user is responsible for taking the necessary precautions to fulfil all local laws and regulations.

Name: W. Goossens
Date: 06.10.2016